

Emufal TE

FDS - Rev. 3
25/11/2008

1. Identification

1.1. Identification of substance or preparation

EMUFAL TE

1.2. Use of the substance or preparation

Bituminous emulsion (water based)n for the preparation of surfaces for waterproofing.

1.3. Company identification

TEXSA SYSTEMS SLU

C/ Ferro, 7

Polígono Industrial Can Pelegrí

08755 - Castellbisbal (Barcelona), SPAIN

Tel: (+34) 93 635 14 00

Fax: (+34) 93 635 14 27

1.4. Emergency phone

Texsa: (+34) 93 635 14 00

2. Composition/Information on the components

2.1. Identification of substance or preparation

Bitumen, water, emulsifiers and rubber.

2.2. a. Representative hazardous substances for health or environment

None

2.3. Substances declared as not classified as hazardous

None

3. Hazard identification

3.1. Main hazards

None

3.2. Specific risks

None

4. First aid

Inhalation:

Inhaling fumes cause irritation of the nose or throat or cough. Go out into fresh air.

Skin contact:

It can cause irritation. Remove contaminated clothing. Wash the skin with properly soap and water. Do not use solvents or thinners

Eye contact:

Wash with abundant fresh, clean water during 10 minutes, keeping the eyelids separated. Send the affected person to an ophthalmologist, specially if eyes are red or there is pain or visual problems.

Ingestion:

If the quantity ingested is small, rinse out mouth with water and seek medical aid. Rest and do NOT provoke vomiting.

5. Fire-fighting measures

5.1. Suitable extinguishing measures:

Foams, dry chemical powder, carbon dioxide, sand and water sprinkler (mist).

5.2. Extinguishing measures not to be used:

In the case of big fires, do not use a water blast

5.3. Special exposure risks:

Formation of thick smoke. Exposure to decay products can entail health risks. Prevent fire fighting effluent from penetrating sewers and waterways.

5.4. Special protection equipment:

Fire-fighting personnel must be equipped with independent, insulating breathing protection against smoke and decay products.