



# DECLARATION OF PERFORMANCE

N° WPSIT0224

Unique identification code of the product-type: **VINITEX MP SC**

Intended uses: **PVC membrane for waterproofing of roofing (EN 13956:2012)**

Manufacturer: **SOPREMA srl  
Via Industriale dell'Isola, 3  
24040 CHIGNOLO D'ISOLA (BG) – Italia  
www.soprema.it**

Authorised representative: **Not applicable**

Systems of AVCP: **System 2+**

Harmonised standard: **EN 13956:2012**

Notifies bodies: **Notified Body No. 1085  
OFI Technologie & Innovation GmbH**

Declared performances:

| Essential characteristics   | Test method                          | Performance   | Harmonised technical specification |
|---|--------------------------------------|---|------------------------------------|
| External fire performance   | EN 13501-5                           | <b>F<sub>ROOF</sub></b>                                       | <b>EN 13956:2012</b>               |
| Reaction to fire  | EN ISO 11925-2<br>EN 13501-1         | <b>E</b>  |                                    |
| Watertightness  | EN 1928 met. B                       | <b>pass</b>   |                                    |
| Tensile properties:<br>- Tensile strength (N/5cm)<br>- Elongation (%)                                     | EN 12311-2 met.A<br>EN 12311-2 met.A | <b>≥ 1100</b><br><b>≥ 15</b>                                  |                                    |
| Resistance to impact (mm)<br>thickness 1,2 mm<br>thickness 1,5 mm<br>thickness 1,8 mm<br>thickness 2,0 mm | EN 12691 met. A                      | <b>≥ 450</b><br><b>≥ 800</b><br><b>≥ 900</b><br><b>≥ 1250</b> |                                    |
| Resistance to static loading (kg)   | EN 12730                             | <b>≥ 20</b>   |                                    |
| Tear resistance (N)   | EN 12310-2                           | <b>≥ 200</b>  |                                    |
| Joint strength:<br>- Peel resistance (N/50mm)<br>- Shear resistance (N/5cm)                               | EN 12316-2<br>EN 12317-2             | <b>≥ 200</b><br><b>&gt; 600</b><br><b>break out joint</b>     |                                    |
| Foldability at low temperature  | EN 495-5                             | <b>≤ -25°C</b>  |                                    |
| Resistance to root  | EN 13948                             | <b>resistant</b>  |                                    |
| Durability:<br>Exposure to UV radiation,<br>elevated temperature and water                                | EN 1297                              | <b>grade 0</b>  |                                    |
| Dangerous substances  | -                                    | <b>conforms</b>   |                                    |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Mr. BROCCANELLO Bruno, Managing Director  
Chignolo d'Isola, 10/09/2018**