

## DRENTEX PERFIL

DRENTEX PERFIL profile made of HDPE for top finishing application on wall drainages

### ADVANTAGES

- Applying DRENTEX PERFIL to the top of the wall prevents the chamber from being contaminated by Texsa Systems DRENTEX series products.

### APPLICATION

- Horizontal protection of drainage systems located in walls.
- Aesthetic finishing and perimeter coating for the top of the wall.

### REGULATIONS

- Quality System in accordance with ISO:9001

## Auxiliary Drainages

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.

## INSTALLATION

- Vertical application: The overlap is applied against the direction of runoff water. This minimizes water leakage behind the drainage system.
- Finally, the adjacent ground is spread and leveled by layers to ensure optimum and proper drainage, taking care to not drag the membrane.
- Anchoring on the upper part of the wall is carried out with DRENTEX PERFIL. • Applying DRENTEX PERFIL to the top of the wall prevents the chamber from being contaminated by Texsa Systems DRENTEX series products.

## Auxiliary Drainages

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.