

## TEXSALON ADHESIVE TPO

Is a flammable, ready-to-use contact adhesive

### APPLICATION

TEXSALON ADHESIVE TPO adhesive is used to join polyolefin TPO waterproofing membranes on vertical surfaces.

### REGULATIONS

Certification of quality system UNI EN ISO 9001 (Business Quality System) and UNI EN ISO 14001 (Environmental System).

### Synthetic Waterproofing TPO

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.

## INSTALLATION

- The support surface must be clean and free of impurities.
- The TEXSALON ADHESIVE TPO adhesive should be spread evenly with a toothbrush or roller, or similar tool, applying it on the entire surface of the two sides to be adhered.
- After checking the state of adherence, press down on the two layers with the metal or rubber roller.
- The adherence is immediate, although the maximum adherence is achieved in a few days.
- Tools can be cleaned with acetone.

## SPECIFIC INSTRUCTIONS:

- Do not use to join polystyrene.

## COVERAGE:

Apply a minimum of about 500 gr/m<sup>2</sup> on the entire surface of the two sides to be adhered. The amounts are merely guidelines and should be evaluated considering the specific circumstances of the space where the product is being applied.

## Synthetic Waterproofing TPO

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.

## PACKAGING AND STORAGE

	Unit	TEXSALON ADHESIVE TPO
Packaging (can)	L	6
Storage conditions	-	Store at room temperature

Shelf-Life The shelf-life is at least 6 months from production date printed on the packaging, provided that the same is stored in a dry place and in original sealed and undamaged container.

## TECHNICAL PROPERTIES

PROPERTIES	Unit	TEXSALON ADHESIVE TPO
Specific weight at 20°C	kg/m <sup>3</sup>	790 ± 10
Water solubility	-	Not soluble
Flamability	-	< 0
Solids	%	30,5 ± 1,0

## Synthetic Waterproofing TPO

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.